

presenting a second networked sales interface through the network for the second accountholder based on input received from the second accountholder, and

wherein the steps of presenting are performed by a provider for the accountholders, and present the first and second networked sales interfaces in such a way that they provide an impression that they are operated by the accountholders, and wherein the steps of presenting present different headers for the first networked sales interface and for the second network sales interface.

Please cancel claims 47-48 without prejudice or disclaimer.

In the Drawings

Please amend Fig. 1 as shown in the attached red-marked sheet. A copy is being provided to the official draftsman under separate cover.

REMARKS

These remarks are in reply to the Office Action mailed December 31, 2003.

Allowable Subject Matter

Claims 18, 19, 27-35 and 38-46 were indicated to be allowable if rewritten in independent form, and these claims have been so rewritten. The remaining claims have been cancelled. This application should therefore now be in condition for allowance, and such action is respectfully requested.

The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to Deposit Account No. 50-0750.

Respectfully submitted,

May 28, 2003
Dated

Kristofer E. Elbing
Kristofer E. Elbing
Registration No. 34,590
187 Pelham Island Road
Wayland, MA 01778
Telephone: (508) 358-2590
Facsimile: (508) 358-0714



Marked-Up Version to Show Changes Made

18. A sales system for coupling to a communications network, comprising:
_____ a first sales interface at a first network address, the first sales interface including a first set of user interface elements,
_____ a second sales interface at a second network address, the second sales interface including a second set of user interface elements,
_____ a sales server at a third network address that operates the first and second sales interfaces while providing an impression that they are being operated by different entities, wherein the sales server includes a customization interface responsive to user input to define the first and second sets of user interface elements, ——— 18. The system of claim 13 wherein the customization interface is a categorization interface responsive to user input to define the first and second sets of categorized interface elements, and wherein the categorization interface elements each include different specification elements.

19. A sales system for coupling to a communications network, comprising:
_____ a first sales interface at a first network address, the first sales interface including a first set of user interface elements,
_____ a second sales interface at a second network address, the second sales interface including a second set of user interface elements,
_____ a sales server at a third network address that operates the first and second sales interfaces while providing an impression that they are being operated by different entities, wherein the sales server includes a customization interface responsive to user input to define the first and second sets of user interface elements, ——— 19. The system of claim 13 wherein the customization interface is a categorization interface responsive to user input to define the first and second sets of categorized interface elements, and wherein the categorization interface elements each include an unused attribute.

27. A sales system for coupling to a communications network, comprising:
_____ a first sales interface at a first network address, the first sales interface including a first set of user interface elements,
_____ a second sales interface at a second network address, the second sales interface including a second set of user interface elements, and

RECEIVED
JUN - 3 2003
TECHNOLOGY CENTER 2809

a sales server at a third network address that operates the first and second sales interfaces while providing an impression that they are being operated by different entities, wherein the sales server includes a customization interface responsive to user input to define the first and second sets of user interface elements, — ~~27. The system of claim 1 wherein the sales server is operative to create the impression that the sales interfaces are being operated by different domains by operating with the address of the first sales interface mapped to a first domain and the address of the second sales interface mapped to a second domain different from the first domain.~~

35. A sales system for coupling to a communications network, comprising:
a first sales interface at a first network address, the first sales interface including a first set of user interface elements,
a second sales interface at a second network address, the second sales interface including a second set of user interface elements, and
a sales server at a third network address that operates the first and second sales interfaces while providing an impression that they are being operated by different entities, wherein the sales server includes a customization interface responsive to user input to define the first and second sets of user interface elements, — ~~35. The system of claim 1 wherein the customization interface is operative to provide different headers for the first sales interface and for the second sales interface.~~

38. A sales method for operation through a communications network, comprising:
receiving customization commands from a first accountholder,
receiving customization commands from a second accountholder,
presenting a first networked sales interface through the network for the first accountholder based on input received from the first accountholder,
presenting a second networked sales interface through the network for the second accountholder based on input received from the second accountholder, and

38. The method of claim 20 wherein the steps of presenting are performed by a provider for the accountholders, and present the first and second networked sales interfaces in such a way that they provide an impression that they are operated by the accountholders, and wherein the steps of presenting present the first networked sales interface at a first domain and present the second networked sales interface at a second domain.

46. A sales method for operation through a communications network, comprising:
receiving customization commands from a first accountholder,
receiving customization commands from a second accountholder,
presenting a first networked sales interface through the network for the first
accountholder based on input received from the first accountholder,
presenting a second networked sales interface through the network for the second
accountholder based on input received from the second accountholder, and

46. The method of claim 20 wherein the steps of presenting are performed by a provider
for the accountholders, and present the first and second networked sales interfaces in such a way
that they provide an impression that they are operated by the accountholders, and wherein the
steps of presenting present different headers for the first networked sales interface and for the
second network sales interface.